

MULTISTATIC SERIES 700 SUPREME – DUAL

SCOPE OF SUPPLY

- | | |
|--|--------|
| a) Integrated 100KV Ininiti Corona Gun (U.S. Patent No.5678770) | 2 Nos. |
| b) Electro pneumatic Control Panel having Smart Tracker™ Peak Performance Monitor & suitable for Corona & Tribo Guns | 2 Nos. |
| c) Equipment Trolley Std with 2 panel rack and in built Air Distribution System | 1 No. |
| d) Stainless Steel Hopper Round- 25Kgs with 2 Pumps | 1 No. |
| e) Set of Nozzles including Flat & Round Spray, Cables, Hoses & Accessories for start up. | 2 Set. |

PNEUMATIC DATA

Maximum input pressure	7 bar
Optimum input pressure	6 bar
Maximum water vapour permitted in compressed air	1.3 g/Nm ³
Maximum oil vapour permitted in compressed air	0.1 ppm
Maximum Compressed air consumption	26.4m ³ / hr(16 CFM)

ELECTRICAL DATA

Single phase AC current, selectable voltages	220V or 230/110V
Frequency	50 / 60 Hz.
Connected loads	130VA
Safety class	IP 54 (P43)
Temperature Range	-2 °C to 50 °C
Nominal Input Voltage	10 V eff.
Output Voltage	100 KVDC -ve (+ve on request)
Nominal Output Current	100 micro amps.