

MITSUBA SYSTEMS (I) LLP

MULTISTATIC SERIES 700 SUPREME (HOPPER TYPE) SCOPE OF SUPPLY

- | | |
|--|--------|
| a) Integrated 100KV Infiniti Corona Gun (U.S. Patent No.5678770) | 1 No. |
| b) Electro pneumatic Control Panel having Smart Tracker™
Peak Performance Monitor & suitable for Corona & Tribo
Guns | 1 No. |
| c) Equipment Trolley Std | 1 No. |
| d) Stainless Steel Hopper Round- 25Kgs with Pump | 1 No. |
| e) Set of Nozzles including Flat & Round Spray, Cables,
Hoses & Accessories for start up. | 1 Set. |

PNEUMATIC DATA

Maximum input pressure	7 bar
Optimum input pressure	6 bar
Maximum water vapour permitted in compressed air	1.3 g/Nm ³
Maximum oil vapour permitted in compressed air	0.1 ppm
Maximum Compressed air consumption	13.2m ³ / hr(8 CFM)

ELECTRICAL DATA

Single phase AC current, selectable voltages	220V or 230/110V
Frequency	50 / 60 Hz.
Connected loads	65VA
Safety class	IP 54 (P43)
Temperature Range	-2 °C to 50 °C
Nominal Input Voltage	10 V eff.
Output Voltage	100 KVDC -ve (+ve on request)
Nominal Output Current	100 micro amps.