

SPRAYRIGHT PORTABLE SERIES PRO (TABLE-TOP TYPE)
SCOPE OF SUPPLY

- | | |
|--|--------|
| a) Integrated 100KV Corona Gun | 1 No. |
| b) Positive charging turbulator type tribo gun (OPTIONAL - TO BE PURCHASED EXTRA) | 1 No. |
| c) Electro pneumatic Control Panel suitable for Corona & Tribo Guns – "Table Top Pro" type | 1 No. |
| d) Clamp – lab Pro type | 1 No. |
| e) Stainless Steel Hopper Round – 2 Kgs with Pump | 1 No. |
| f) Set of Nozzles including Flat & Round Spray, Cables, Hoses & Accessories for start up. | 1 Set. |

PNEUMATIC DATA

Maximum input pressure	7 bar
Optimum input pressure	6 bar
Maximum water vapour permitted in compressed air	1.3 g/Nm ³
Maximum oil vapour permitted in compressed air	0.1 ppm
Maximum Compressed air consumption	13.2m ³ / hr (8 CFM)

ELECTRICAL DATA

Single phase AC current, selectable voltages	220V or 230/110V
Frequency	50 / 60 Hz.
Connected loads	65VA
Safety class	IP 54 (P43)
Temperature Range	-2 °C to 50 °C
Nominal Input Voltage	10 V eff.
Output Voltage	Fixed 100 KVDC & 70 KVDC -ve only (+ve on request)
Nominal Output Current	100 micro amps.