

# FBE COATING GUN

Specially Designed for Pipe & Re-bar Coating

## Features

- ▶ Standard Gun powder flow 0 to 30 Kg/hr (Suitable for Re-bar and Conventional 3 layer pipe coating).
- ▶ High Flow Gun powder flow 0 to 70 Kg/hr (Suitable for new generation pipe coating requiring film thickness of 1000 microns. Also suitable for conventional 3 layer pipe coating).
- ▶ Integrated 100 KV - No HV Cable.
- ▶ Highest Transfer Efficiency with Air Rinse System to clean electrodes & deflector / flat spray nozzles to optimize transfer efficiency.
- ▶ Also available with Low Flow Version.
- ▶ Control Panel with Performance Monitor.
- ▶ Control Panel Meets IP54 standards.



**STANDARD Infiniti™ GUN**  
(U.S. Patent No. 5678770)  
CAPACITY 0 - 30 Kg/hr.



**High Flow GUN**  
CAPACITY 0 - 70 Kg/hr.

ISO 9001 : 2000 CERTIFIED

**MITSUBA**  
SYSTEMS

34/H, Laxmi Industrial Estate, New Link Road, Andheri (W), Mumbai 400 053. India

Tel: +91 22 2631 8633/ 6692 4151-52-53 Fax: +91 22 6692 4154.

Email: [mitsuba@vsnl.com](mailto:mitsuba@vsnl.com) Website: <http://www.powdergun.com>