## FUNCTIONAL COATING POWDER SPRAY SYSTEM SCOPE OF SUPPLY

Please click on the following link to view and print the complete scope of supply of the Multistatic Corona Series 700:

http://www.powdergun.com/coronahopper.htm

a)	Integrated 100KV Corona Gun	1 No.
b)	Electro pneumatic Control Panel having Smart Tracker™ Peak Performance Monitor & suitable for Corona & Tribo Guns	1 No.
c)	Equipment Trolley Std	1 No.
d)	Stainless Steel Hopper Round- 5 kgs / 10 kgs with Pump	1 No.
e)	ELECTROSMART Powder Hose and 1 box SMART BULLETS – The Ultra quick Colour change tool Set of Nozzles including Flat & Round Spray, Cables & Accessories for start up.	1 Set.

## PNEUMATIC DATA

Maximum input pressure	7 bar
Optimum input pressure	6 bar
Maximum water vapour content in compressed air	1.3 g/Nm <sup>3</sup>
Maximum oil vapour content in compressed air	0.1 ppm
Maximum Compressed air consumption	13.2m <sup>3</sup> / hr

## **ELECTRICAL DATA**

Single phase AC current, selectable voltages	220V or 230/110V
Frequency	50 / 60 Hz.
Connected loads	65VA
Safety class	IP 54 (P43)
Temperature Range	2 ⊗C to 50 ⊗C
Nominal Input Voltage	10 V eff.
Output Voltage	100 KVDC +ve
Nominal Output Current	100 micro amps.